



**METAFRAX  
CHEMICALS**

## **GRANULATED POLYAMIDE 6**

### **Application**

Product is produced for casting of the industrial-use parts applied in machine industry, motor vehicle industry and other fields of nation's economy.

### **Packaging**

PP bags with plastic liner net weight 25kg.

### **Transportation and storage**

Product is transported by all modes of transport in closed transport facilities according to the rules of goods carriage valid for this mode of transport. Product is stored in sheltered well-ventilated storage facilities, protected from atmosphere precipitation and direct sunlight and at a distance of no less than 1 m from the heating units.

### **Manufacturer's guaranty**

Guaranty period of storage to be 1 year from the manufacturing date, provided that all transportation and shipment rules are observed.

### **Purchasing of the product**

PJSC Metafrax  
Aleksandr Protasov  
Phone: +7 342 489 27 64, +7 342 489 28 83  
Fax: +7 342 484 72 27  
E-mail: [Sale@metafrax.ru](mailto:Sale@metafrax.ru)



## Main physical and chemical features

Parameter name	Norm	
	ПА 6 granulated	ПА 6-МГ granulated
Appearance and color	Granules of grey to yellow – brown color	Granules of dark-grey to black color
Number of foreign particles per 100 g of product, pcs., no more	100	–
Granula size in mm (length)	4±2	5±2
Moisture mass fraction, %, no more	0,5	0,7
Mass fraction of unhewn granulas with length up to 20 mm, %, no more	1,5	2,0
ПА 6-МГ – ПА 6 modified with graphite		